

Beam Clamp TCS 1 HCP





General Information

Heavy-duty connection elements which, in combination with Grub Screws (M10), are suitable for mounting pipes, ducts and equipment to steel beams (I-, T-, U- and angle steel beams). The combination with a Universal Joint ss provides for vertically aligned attachment to inclined beams. Can serve as single mounting elements, for installing crossbars and for fixing cantilever structures. Due to their special base profile, Beam Clamps TCS 1 can also be slid along and retained in the opening of Sikla Channels MS 41.

Installation

Tighten the clamping bolt of the Beam Clamp first by hand, then tighten down with a spanner according to the mounting instructions. The hardened point of the clamping bolt will penetrate the comparatively soft material of the beam, ensuring a solid and highly secure connection. Tighten the locking nut for securing the installation.
Use an additional Holding Bracket HK 41 for mounting in the aera of the cutting edge of a channel.
Clamping range on parallel flange: 26 mm
Advice: Read relevant mounting instructions before installation!

Material Properties

Halogen-free	0
UV-resistant	0

Material

Primary element material	cast steel
Connecting element material	steel
Surface finish	HCP
Corrosion protection class	C4

Forces

Type	-V{X,perm.}	V{X,perm.}	V{Y,perm.}	-V{Z,perm.}
TCS 1 M10/M10 HCP	3,11 kN	3,11 kN	1,83 kN	5,00 kN

Note on loadings

The nominal loads indicated apply to new Beam Clamps fixed to undamaged beam flanges only.

Types

Type	Max. flange thickness	Thread connection	Weight	Quantity	Part number
TCS 1 M10/M10 HCP	26,00 mm	M10/M10	0,223 kg/pcs.	50 pcs.	162151

Dimensions

Type	B	B1	H1	L	L2	Ma	Mi1	Mi2
TCS 1 M10/M10 HCP	33 mm	21,5 mm	26,2 mm	44 mm	23 mm	M10	M10	M10

Certification

Approved and accepted by VdS and FM for use with stationary fire extinguishing systems. For different application fields see documents.

Documents

VdS Approval - Sikla Beam Clamp TCS 1 M10/M10 - G4820023

VdS Approval - Sikla Beam Clamp TCS with Safety Strap - G4800040

FM Approval - Sikla Beam Clamps TCS

VdS Approval - Sikla Beam Clamp TCS 1 - G4800039