Brass Anchor ANM



General Information

Brass Anchors with metric thread which have a gentle cone and a milled surface. They guarantee high holding forces, are safe against rotation and are anti-skidding. No need of special drills. Suitable for concrete, solid brick, natural stones, clinker brick, sand-lime bricks, solid wood and laminated timber. For fixing of channels, brackets, pipelines etc. Not suitable for humidors.

Installation

Put the anchor flush to the anchoring base, i.e. under plaster and insulating layers. After tapping the anchor in, a special surface structure prevents rotation in the drill hole. The brass expansion anchor is suitable for processing with metric bolts, which spread the anchor while tightening.

Material Properties

Halogen-free	0
UV-resistant	0

Material

Primary element material	Brass
Corrosion protection class	C2

Additional information

Delivery date upon request - goods are procured on an order-by-order basis.

Types

Type	L	Weight	Quantity	Part number
ANM M 8	27,50 mm	0,007 kg/pcs.	100 pcs.	402420
ANM M 10	32,00 mm	0,012 kg/pcs.	100 pcs.	402421
ANM M 12	38,00 mm	0,024 kg/pcs.	50 pcs.	402422
ANM M 16	45,00 mm	0,046 kg/pcs.	25 pcs.	402423

Certification

epd-global
Powered by EPD-Norway

Documents

Brass Anchor ANM - Technical Data