



Pipe Shoe LA-HV 200 HCP









General Information

Height-adjustable, single-clamp pipe shoe with a delivery height of 200 mm. Height adjustment in steps of 2.5 mm. Particularly suitable for sliding pipe supports on suitable surfaces. When resting on steel beams, a minimum flange width of 80 mm is recommended. Guide or fixed points can also be created in combination with other Sikla components.

Installation

Typ	Height H as delivered [mm]	Height H Range [mm]
HV 200	200	171 - 223,5

Tightening torque screw connections

Clamping bolts	Tightening torque [Nm]	Height adjustment	Tightening torque [Nm]
DN 15 - 40	40	Bolts in the bar	80
DN 50 - 150	50	Bolts in the bar	80

Temperature

Max. temperature	300 °C
Min. temperature	-20 °C
Max. temperature sliding element	130 °C
Min. temperature sliding element	-20 °C

Mechanical Properties

Pipe shoe static coefficient of friction u (without sliding plate) - siFramo and siMotec	0,3


Material Properties


Halogen-free	0
UV-resistant	0


Material

Primary element material	steel
Sliding element material	PA 6.0
Surface finish	HCP
Corrosion protection class	C4

Pipe Shoe LA-HV 200 HCP







Additional information

Also available with DualShield for high corrosion protection within C5H environments. Delivery time on request - Made-to-order goods.

Types

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
LA-HV 200 14-18	14,00 mm	18,00 mm		3,48 kg/pcs.	1 pcs.	801699
LA-HV 200 18-22 (DN 15) HCP	18,00 mm	22,00 mm	DN 15 (1/2")	3,46 kg/pcs.	1 pcs.	112390
LA-HV 200 23-27 (DN 20) HCP	23,00 mm	27,00 mm	DN 20 (3/4")	3,48 kg/pcs.	1 pcs.	112391
LA-HV 200 26-30	26,00 mm	30,00 mm		3,53 kg/pcs.	1 pcs.	801700
LA-HV 200 30-34 (DN 25) HCP	30,00 mm	34,00 mm	DN 25 (1")	3,5 kg/pcs.	1 pcs.	110053
LA-HV 200 35-39	35,00 mm	39,00 mm		3,566 kg/pcs.	1 pcs.	801701
LA-HV 200 40-44 (DN 32) HCP	40,00 mm	44,00 mm	DN 32 (1 1/4")	3,6 kg/pcs.	1 pcs.	110054
LA-HV 200 45-49 (DN 40) HCP	45,00 mm	49,00 mm	DN 40 (1 1/2")	3,6 kg/pcs.	1 pcs.	110055
LA-HV 200 50-54	50,00 mm	54,00 mm		3,624 kg/pcs.	1 pcs.	801702
LA-HV 200 55-59	55,00 mm	59,00 mm		3,642 kg/pcs.	1 pcs.	801703
LA-HV 200 57-61 (DN 50) HCP	57,00 mm	61,00 mm	DN 50 (2")	3,8 kg/pcs.	1 pcs.	110056
LA-HV 200 62-66	62,00 mm	66,00 mm		3,846 kg/pcs.	1 pcs.	801704
LA-HV 200 67-71	67,00 mm	71,00 mm		3,872 kg/pcs.	1 pcs.	801705
LA-HV 200 72-77 (DN 65) HCP	72,00 mm	77,00 mm	DN 65 (2 1/2")	3,9 kg/pcs.	1 pcs.	110057
LA-HV 200 78-83	78,00 mm	83,00 mm		3,926 kg/pcs.	1 pcs.	801706
LA-HV 200 84-89 (DN 80) HCP	84,00 mm	89,00 mm	DN 80 (3")	3,9 kg/pcs.	1 pcs.	110058
LA-HV 200 89-95	89,00 mm	95,00 mm		4,134 kg/pcs.	1 pcs.	801707
LA-HV 200 96-102	96,00 mm	102,00 mm		4,176 kg/pcs.	1 pcs.	801708
LA-HV 200 102-109	102,00 mm	109,00 mm		4,218 kg/pcs.	1 pcs.	801709
LA-HV 200 109-115 (DN 100) HCP	109,00 mm	115,00 mm	DN 100 (4")	4,3 kg/pcs.	1 pcs.	110059

Pipe Shoe LA-HV 200 HCP

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
LA-HV 200 115-122	115,00 mm	122,00 mm		4,3 kg/pcs.	1 pcs.	801710
LA-HV 200 122-128	122,00 mm	128,00 mm		4,336 kg/pcs.	1 pcs.	801711
LA-HV 200 128-134	128,00 mm	134,00 mm		4,374 kg/pcs.	1 pcs.	801712
LA-HV 200 134-140 (DN 125) HCP	134,00 mm	140,00 mm	DN 125 (5")	4,4 kg/pcs.	1 pcs.	110060
LA-HV 200 140-146	140,00 mm	146,00 mm		4,446 kg/pcs.	1 pcs.	801713
LA-HV 200 146-152	146,00 mm	152,00 mm		4,486 kg/pcs.	1 pcs.	801714
LA-HV 200 152-158	152,00 mm	158,00 mm		4,524 kg/pcs.	1 pcs.	801715
LA-HV 200 157-163	157,00 mm	163,00 mm		4,554 kg/pcs.	1 pcs.	801716
LA-HV 200 163-169 (DN 150) HCP	163,00 mm	169,00 mm	DN 150 (6")	5,4 kg/pcs.	1 pcs.	110061

Dimensions

Type	b	B2	D	D1	H	HV min	HV max	L2	SG	SL	t	W
LA-HV 200 14-18	30 mm	105 mm	18 mm	18 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 18-22 (DN 15) HCP	30 mm	105 mm	22 mm	22 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 23-27 (DN 20) HCP	30 mm	105 mm	27 mm	27 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 26-30	30 mm	105 mm	30 mm	30 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 30-34 (DN 25) HCP	30 mm	105 mm	34 mm	34 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 35-39	30 mm	105 mm	39 mm	39 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 40-44 (DN 32) HCP	30 mm	105 mm	44 mm	44 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 45-49 (DN 40) HCP	30 mm	105 mm	49 mm	49 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 50-54	30 mm	105 mm	54 mm	54 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°
LA-HV 200 55-59	30 mm	105 mm	59 mm	59 mm	200 mm	171 mm	223,5 mm	255,6 mm	M10	40 mm	5 mm	90°

Pipe Shoe LA-HV 200 HCP

Type	b	B2	D	D1	H	HV min	HV max	L2	SG	SL	t	W
LA-HV 200 57-61 (DN 50) HCP	40 mm	105 mm	61 mm	61 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 62-66	40 mm	105 mm	66 mm	66 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 67-71	40 mm	105 mm	71 mm	71 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 72-77 (DN 65) HCP	40 mm	105 mm	77 mm	77 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 78-83	40 mm	105 mm	83 mm	83 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 84-89 (DN 80) HCP	40 mm	105 mm	89 mm	89 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 89-95	50 mm	105 mm	95 mm	95 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 96-102	50 mm	105 mm	102 mm	102 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 102-109	50 mm	105 mm	109 mm	109 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	45 mm	5 mm	90°
LA-HV 200 109-115 (DN 100) HCP	50 mm	105 mm	115 mm	115 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 115-122	50 mm	105 mm	122 mm	122 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 122-128	50 mm	105 mm	128 mm	128 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 128-134	50 mm	105 mm	134 mm	134 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 134-140 (DN 125) HCP	50 mm	105 mm	140 mm	140 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 140-146	50 mm	105 mm	146 mm	146 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 146-152	50 mm	105 mm	152 mm	152 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 152-158	50 mm	105 mm	158 mm	158 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 157-163	50 mm	105 mm	163 mm	163 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	50 mm	5 mm	45°
LA-HV 200 163-169 (DN 150) HCP	50 mm	105 mm	169 mm	169 mm	200 mm	171 mm	223,5 mm	255,6 mm	M12	55 mm	5 mm	45°

Pipe Shoe LA-HV 200 HCP

Certification

Documents

Sikla Pipe Supports - Comprehensive Solutions for Secure and Efficient Installations

Load Capacities for Pipe Supports LA HV - Sikla Technical Data

Pipe Shoes LA-HV Type Overview