


Pipe Clamp STABIL RB-A HCP







General Information

For particularly high static requirements in plant construction. Design similar to DIN 3567. The perforations on both sides allow the application of standardised bolts and threaded nuts out of the Sikla product range.

Installation

Tightening torque and recommended clamping bolts:

Size range [mm]	Recommended clamping bolts	Tightening torque [Nm]
14 - 49	M10 x 40	20
57 - 109	M12 x 45	40
109 - 163	M12 x 50	40
163 - 273	M12 x 55	40
317 - 374	M16 x 60	100
397 - 610	M16 x 65	100

Material Properties

Halogen-free	0
UV-resistant	0

Material

Primary element material	steel
Surface finish	HCP
Corrosion protection class	C4

Forces

Type	-V{Z,perm.}
STABIL RB-A 14- 18 HCP	11,00 kN
STABIL RB-A 18- 22 HCP	11,00 kN
STABIL RB-A 23- 27 HCP	11,00 kN
STABIL RB-A 26- 30 HCP	11,00 kN
STABIL RB-A 30- 34 HCP	11,00 kN
STABIL RB-A 35- 39 HCP	11,00 kN
STABIL RB-A 40- 44 HCP	11,00 kN
STABIL RB-A 45- 49 HCP	11,00 kN
STABIL RB-A 50- 54 HCP	11,00 kN

Pipe Clamp STABIL RB-A HCP

Type	-V{Z,perm.}
STABIL RB-A 55- 59 HCP	11,00 kN
STABIL RB-A 57- 61 HCP	15,50 kN
STABIL RB-A 62- 66 HCP	15,50 kN
STABIL RB-A 67- 71 HCP	15,50 kN
STABIL RB-A 72- 77 HCP	15,50 kN
STABIL RB-A 78- 83 HCP	15,50 kN
STABIL RB-A 84- 89 HCP	15,50 kN
STABIL RB-A 89- 95 HCP	15,50 kN
STABIL RB-A 96- 102 HCP	22,00 kN
STABIL RB-A 102- 109 HCP	22,00 kN
STABIL RB-A 109- 115 HCP	22,00 kN
STABIL RB-A 115- 122 HCP	22,00 kN
STABIL RB-A 122- 128 HCP	22,00 kN
STABIL RB-A 128- 134 HCP	22,00 kN
STABIL RB-A 134- 140 HCP	22,00 kN
STABIL RB-A 140- 146 HCP	22,00 kN
STABIL RB-A 146- 152 HCP	22,00 kN
STABIL RB-A 152- 158 HCP	22,00 kN
STABIL RB-A 157- 163 HCP	22,00 kN
STABIL RB-A 163- 169 HCP	22,00 kN
STABIL RB-A 168- 174 HCP	42,00 kN
STABIL RB-A 174- 180 HCP	42,00 kN
STABIL RB-A 181- 187 HCP	42,00 kN
STABIL RB-A 188- 194 HCP	42,00 kN
STABIL RB-A 194- 200 HCP	42,00 kN
STABIL RB-A 201- 207 HCP	42,00 kN
STABIL RB-A 208- 214 HCP	42,00 kN
STABIL RB-A 215- 221 HCP	42,00 kN
STABIL RB-A 222- 229 HCP	42,00 kN
STABIL RB-A 230- 237 HCP	42,00 kN
STABIL RB-A 238- 245 HCP	42,00 kN
STABIL RB-A 246- 254 HCP	42,00 kN
STABIL RB-A 255- 262 HCP	42,00 kN
STABIL RB-A 259- 266 HCP	42,00 kN
STABIL RB-A 266- 273 HCP	42,00 kN

Pipe Clamp STABIL RB-A HCP

Type	-V{Z,perm.}
STABIL RB-A 274- 282 HCP	42,00 kN
STABIL RB-A 283- 291 HCP	42,00 kN
STABIL RB-A 292- 300 HCP	42,00 kN
STABIL RB-A 301- 309 HCP	42,00 kN
STABIL RB-A 310- 317 HCP	42,00 kN
STABIL RB-A 317- 324 HCP	42,00 kN
STABIL RB-A 325- 333 HCP	42,00 kN
STABIL RB-A 334- 342 HCP	42,00 kN
STABIL RB-A 343- 350 HCP	42,00 kN
STABIL RB-A 349- 356 HCP	42,00 kN
STABIL RB-A 358- 365 HCP	42,00 kN
STABIL RB-A 366- 374 HCP	42,00 kN
STABIL RB-A 375- 382 HCP	42,00 kN
STABIL RB-A 381- 388 HCP	42,00 kN
STABIL RB-A 389- 396 HCP	42,00 kN
STABIL RB-A 397- 407 HCP	42,00 kN
STABIL RB-A 408- 418 HCP	42,00 kN
STABIL RB-A 419- 429 HCP	42,00 kN
STABIL RB-A 430- 440 HCP	42,00 kN
STABIL RB-A 441- 451 HCP	42,00 kN
STABIL RB-A 447- 457 HCP	42,00 kN
STABIL RB-A 458- 468 HCP	42,00 kN
STABIL RB-A 467- 477 HCP	42,00 kN
STABIL RB-A 477- 487 HCP	42,00 kN
STABIL RB-A 488- 498 HCP	42,00 kN
STABIL RB-A 498- 508 HCP	42,00 kN
STABIL RB-A 509- 519 HCP	42,00 kN
STABIL RB-A 520- 530 HCP	42,00 kN
STABIL RB-A 531- 541 HCP	42,00 kN
STABIL RB-A 542- 552 HCP	42,00 kN
STABIL RB-A 553- 563 HCP	42,00 kN
STABIL RB-A 564- 574 HCP	42,00 kN
STABIL RB-A 575- 585 HCP	42,00 kN
STABIL RB-A 586- 596 HCP	42,00 kN
STABIL RB-A 594- 604 HCP	42,00 kN

Pipe Clamp STABIL RB-A HCP

Type	-V{Z,perm.}
STABIL RB-A 600- 610 HCP	42,00 kN

Note on loadings

Admissible load valid with fixation on both sides.
The max. permissible load capacity of the connected parts (e.g. anchors) shall be considered.
The max. adm. load capacity is determined by the application of statistical methods resulting from the breaking loads, under observance of a max. adm. deformation of 1.5 mm resp. 2% of the max. stretchable pipe dia.

Types

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
STABIL RB-A 14- 18 HCP	14,00 mm	18,00 mm	DN 8 (1/4")	0,170 kg/ pcs.	25 pcs.	112790
STABIL RB-A 18- 22 HCP	18,00 mm	22,00 mm	DN 15 (1/2")	0,180 kg/ pcs.	25 pcs.	112791
STABIL RB-A 23- 27 HCP	23,00 mm	27,00 mm	DN 20 (3/4")	0,190 kg/ pcs.	25 pcs.	112792
STABIL RB-A 26- 30 HCP	26,00 mm	30,00 mm		0,232 kg/ pcs.	25 pcs.	804246
STABIL RB-A 30- 34 HCP	30,00 mm	34,00 mm	DN 25 (1")	0,220 kg/ pcs.	25 pcs.	112793
STABIL RB-A 35- 39 HCP	35,00 mm	39,00 mm	DN 25 (1")	0,240 kg/ pcs.	25 pcs.	112794
STABIL RB-A 40- 44 HCP	40,00 mm	44,00 mm	DN 32 (1 1/4")	0,260 kg/ pcs.	25 pcs.	112795
STABIL RB-A 45- 49 HCP	45,00 mm	49,00 mm	DN 40 (1 1/2")	0,280 kg/ pcs.	25 pcs.	112796
STABIL RB-A 50- 54 HCP	50,00 mm	54,00 mm		0,328 kg/ pcs.	25 pcs.	804247
STABIL RB-A 55- 59 HCP	55,00 mm	59,00 mm		0,346 kg/ pcs.	25 pcs.	804248
STABIL RB-A 57- 61 HCP	57,00 mm	61,00 mm	DN 50 (2")	0,420 kg/ pcs.	25 pcs.	112797
STABIL RB-A 62- 66 HCP	62,00 mm	66,00 mm		0,502 kg/ pcs.	25 pcs.	804249
STABIL RB-A 67- 71 HCP	67,00 mm	71,00 mm		0,460 kg/ pcs.	25 pcs.	112798
STABIL RB-A 72- 77 HCP	72,00 mm	77,00 mm	DN 65 (2 1/2")	0,520 kg/ pcs.	25 pcs.	112799
STABIL RB-A 78- 83 HCP	78,00 mm	83,00 mm		0,586 kg/ pcs.	25 pcs.	804250
STABIL RB-A 84- 89 HCP	84,00 mm	89,00 mm	DN 80 (3")	0,610 kg/ pcs.	25 pcs.	112800

Pipe Clamp STABIL RB-A HCP

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
STABIL RB-A 89- 95 HCP	89,00 mm	95,00 mm		0,780 kg/ pcs.	10 pcs.	801958
STABIL RB-A 96- 102 HCP	96,00 mm	102,00 mm	DN 90 (3 1/2")	0,760 kg/ pcs.	10 pcs.	112801
STABIL RB-A 102- 109 HCP	102,00 mm	109,00 mm	DN 100 (4")	0,830 kg/ pcs.	10 pcs.	112802
STABIL RB-A 109- 115 HCP	109,00 mm	115,00 mm	DN 100 (4")	0,870 kg/ pcs.	10 pcs.	112803
STABIL RB-A 115- 122 HCP	115,00 mm	122,00 mm		0,940 kg/ pcs.	10 pcs.	801959
STABIL RB-A 122- 128 HCP	122,00 mm	128,00 mm		0,980 kg/ pcs.	10 pcs.	801960
STABIL RB-A 128- 134 HCP	128,00 mm	134,00 mm	DN 125 (5")	0,930 kg/ pcs.	10 pcs.	112804
STABIL RB-A 134- 140 HCP	134,00 mm	140,00 mm	DN 125 (5")	1,010 kg/ pcs.	10 pcs.	112805
STABIL RB-A 140- 146 HCP	140,00 mm	146,00 mm		1,120 kg/ pcs.	10 pcs.	804251
STABIL RB-A 146- 152 HCP	146,00 mm	152,00 mm		1,160 kg/ pcs.	10 pcs.	804252
STABIL RB-A 152- 158 HCP	152,00 mm	158,00 mm		1,200 kg/ pcs.	10 pcs.	804253
STABIL RB-A 157- 163 HCP	157,00 mm	163,00 mm	DN 150 (6")	1,194 kg/ pcs.	10 pcs.	112806
STABIL RB-A 163- 169 HCP	163,00 mm	169,00 mm	DN 150 (6")	2,006 kg/ pcs.	10 pcs.	112807
STABIL RB-A 168- 174 HCP	168,00 mm	174,00 mm		2,092 kg/ pcs.	1 pcs.	804254
STABIL RB-A 174- 180 HCP	174,00 mm	180,00 mm		2,150 kg/ pcs.	1 pcs.	804255
STABIL RB-A 181- 187 HCP	181,00 mm	187,00 mm		2,220 kg/ pcs.	1 pcs.	804256
STABIL RB-A 188- 194 HCP	188,00 mm	194,00 mm	DN 175 (7")	2,160 kg/ pcs.	1 pcs.	112808
STABIL RB-A 194- 200 HCP	194,00 mm	200,00 mm		2,356 kg/ pcs.	1 pcs.	804257
STABIL RB-A 201- 207 HCP	201,00 mm	207,00 mm		2,426 kg/ pcs.	1 pcs.	804258
STABIL RB-A 208- 214 HCP	208,00 mm	214,00 mm		2,494 kg/ pcs.	1 pcs.	804259
STABIL RB-A 215- 221 HCP	215,00 mm	221,00 mm	DN 200 (8")	2,522 kg/ pcs.	1 pcs.	112809

Pipe Clamp STABIL RB-A HCP

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
STABIL RB-A 222- 229 HCP	222,00 mm	229,00 mm		2,634 kg/ pcs.	1 pcs.	804260
STABIL RB-A 230- 237 HCP	230,00 mm	237,00 mm		2,712 kg/ pcs.	1 pcs.	804261
STABIL RB-A 238- 245 HCP	238,00 mm	245,00 mm		2,792 kg/ pcs.	1 pcs.	804262
STABIL RB-A 246- 254 HCP	246,00 mm	254,00 mm		2,800 kg/ pcs.	1 pcs.	112810
STABIL RB-A 255- 262 HCP	255,00 mm	262,00 mm		2,910 kg/ pcs.	1 pcs.	801961
STABIL RB-A 259- 266 HCP	259,00 mm	266,00 mm	DN 250 (10")	2,920 kg/ pcs.	1 pcs.	112811
STABIL RB-A 266- 273 HCP	266,00 mm	273,00 mm	DN 250 (10")	3,550 kg/ pcs.	1 pcs.	112812
STABIL RB-A 274- 282 HCP	274,00 mm	282,00 mm		3,860 kg/ pcs.	1 pcs.	804263
STABIL RB-A 283- 291 HCP	283,00 mm	291,00 mm		3,968 kg/ pcs.	1 pcs.	804264
STABIL RB-A 292- 300 HCP	292,00 mm	300,00 mm		4,076 kg/ pcs.	1 pcs.	804265
STABIL RB-A 301- 309 HCP	301,00 mm	309,00 mm		4,184 kg/ pcs.	1 pcs.	804266
STABIL RB-A 310- 317 HCP	310,00 mm	317,00 mm		4,280 kg/ pcs.	1 pcs.	804267
STABIL RB-A 317- 324 HCP	317,00 mm	324,00 mm	DN 300 (12")	4,110 kg/ pcs.	1 pcs.	112813
STABIL RB-A 325- 333 HCP	325,00 mm	333,00 mm		4,480 kg/ pcs.	1 pcs.	804268
STABIL RB-A 334- 342 HCP	334,00 mm	342,00 mm		4,588 kg/ pcs.	1 pcs.	804269
STABIL RB-A 343- 350 HCP	343,00 mm	350,00 mm		4,684 kg/ pcs.	1 pcs.	804270
STABIL RB-A 349- 356 HCP	349,00 mm	356,00 mm	DN 350 (14")	4,530 kg/ pcs.	1 pcs.	112814
STABIL RB-A 358- 365 HCP	358,00 mm	365,00 mm		4,780 kg/ pcs.	1 pcs.	801962
STABIL RB-A 366- 374 HCP	366,00 mm	374,00 mm	DN 350 (14")	4,840 kg/ pcs.	1 pcs.	112815
STABIL RB-A 375- 382 HCP	375,00 mm	382,00 mm		5,068 kg/ pcs.	1 pcs.	804271
STABIL RB-A 381- 388 HCP	381,00 mm	388,00 mm		5,140 kg/ pcs.	1 pcs.	804272

Pipe Clamp STABIL RB-A HCP

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
STABIL RB-A 389- 396 HCP	389,00 mm	396,00 mm		5,236 kg/ pcs.	1 pcs.	804273
STABIL RB-A 397- 407 HCP	397,00 mm	407,00 mm	DN 400 (16")	6,150 kg/ pcs.	1 pcs.	112816
STABIL RB-A 408- 418 HCP	408,00 mm	418,00 mm		6,260 kg/ pcs.	1 pcs.	801963
STABIL RB-A 419- 429 HCP	419,00 mm	429,00 mm	DN 400 (16")	6,300 kg/ pcs.	1 pcs.	112817
STABIL RB-A 430- 440 HCP	430,00 mm	440,00 mm		6,680 kg/ pcs.	1 pcs.	804274
STABIL RB-A 441- 451 HCP	441,00 mm	451,00 mm		6,834 kg/ pcs.	1 pcs.	804275
STABIL RB-A 447- 457 HCP	447,00 mm	457,00 mm	DN 450 (18")	6,850 kg/ pcs.	1 pcs.	112818
STABIL RB-A 458- 468 HCP	458,00 mm	468,00 mm		7,072 kg/ pcs.	1 pcs.	804276
STABIL RB-A 467- 477 HCP	467,00 mm	477,00 mm		7,198 kg/ pcs.	1 pcs.	804277
STABIL RB-A 477- 487 HCP	477,00 mm	487,00 mm		7,338 kg/ pcs.	1 pcs.	804278
STABIL RB-A 488- 498 HCP	488,00 mm	498,00 mm		7,492 kg/ pcs.	1 pcs.	804279
STABIL RB-A 498- 508 HCP	498,00 mm	508,00 mm	DN 500 (20")	7,660 kg/ pcs.	1 pcs.	112819
STABIL RB-A 509- 519 HCP	509,00 mm	519,00 mm		7,650 kg/ pcs.	1 pcs.	801964
STABIL RB-A 520- 530 HCP	520,00 mm	530,00 mm	DN 500 (20")	7,850 kg/ pcs.	1 pcs.	112820
STABIL RB-A 531- 541 HCP	531,00 mm	541,00 mm		7,910 kg/ pcs.	1 pcs.	112821
STABIL RB-A 542- 552 HCP	542,00 mm	552,00 mm		8,258 kg/ pcs.	1 pcs.	804280
STABIL RB-A 553- 563 HCP	553,00 mm	563,00 mm		8,414 kg/ pcs.	1 pcs.	804281
STABIL RB-A 564- 574 HCP	564,00 mm	574,00 mm		8,568 kg/ pcs.	1 pcs.	804282
STABIL RB-A 575- 585 HCP	575,00 mm	585,00 mm		8,722 kg/ pcs.	1 pcs.	804283
STABIL RB-A 586- 596 HCP	586,00 mm	596,00 mm		8,878 kg/ pcs.	1 pcs.	804284
STABIL RB-A 594- 604 HCP	594,00 mm	604,00 mm		8,990 kg/ pcs.	1 pcs.	804285

Pipe Clamp STABIL RB-A HCP

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
STABIL RB-A 600- 610 HCP	600,00 mm	610,00 mm	DN 600 (24")	8,942 kg/ pcs.	1 pcs.	112822

Dimensions

Type	B1	b1	D	D1	d	e	H	t
STABIL RB-A 14- 18 HCP	80 mm	30 mm	18 mm	18 mm	11 mm	52 mm	28 mm	5 mm
STABIL RB-A 18- 22 HCP	86 mm	30 mm	22 mm	22 mm	11 mm	58 mm	32 mm	5 mm
STABIL RB-A 23- 27 HCP	93 mm	30 mm	27 mm	27 mm	11 mm	65 mm	37 mm	5 mm
STABIL RB-A 26- 30 HCP	97 mm	30 mm	30 mm	30 mm	11 mm	69 mm	40 mm	5 mm
STABIL RB-A 30- 34 HCP	102 mm	30 mm	34 mm	34 mm	11 mm	74 mm	44 mm	5 mm
STABIL RB-A 35- 39 HCP	108 mm	30 mm	39 mm	39 mm	11 mm	80 mm	49 mm	5 mm
STABIL RB-A 40- 44 HCP	114 mm	30 mm	44 mm	44 mm	11 mm	86 mm	54 mm	5 mm
STABIL RB-A 45- 49 HCP	119 mm	30 mm	49 mm	49 mm	11 mm	91 mm	59 mm	5 mm
STABIL RB-A 50- 54 HCP	125 mm	30 mm	54 mm	54 mm	11 mm	97 mm	64 mm	5 mm
STABIL RB-A 55- 59 HCP	130 mm	30 mm	59 mm	59 mm	11 mm	102 mm	69 mm	5 mm
STABIL RB-A 57- 61 HCP	136 mm	40 mm	61 mm	61 mm	13 mm	103 mm	71 mm	5 mm
STABIL RB-A 62- 66 HCP	141 mm	40 mm	66 mm	66 mm	13 mm	108 mm	76 mm	5 mm
STABIL RB-A 67- 71 HCP	147 mm	40 mm	71 mm	71 mm	13 mm	114 mm	81 mm	5 mm
STABIL RB-A 72- 77 HCP	152 mm	40 mm	77 mm	77 mm	13 mm	119 mm	87 mm	5 mm
STABIL RB-A 78- 83 HCP	159 mm	40 mm	83 mm	83 mm	13 mm	126 mm	93 mm	5 mm
STABIL RB-A 84- 89 HCP	165 mm	40 mm	89 mm	89 mm	13 mm	132 mm	99 mm	5 mm
STABIL RB-A 89- 95 HCP	171 mm	50 mm	95 mm	95 mm	13 mm	138 mm	105 mm	5 mm
STABIL RB-A 96- 102 HCP	178 mm	50 mm	102 mm	102 mm	13 mm	145 mm	112 mm	5 mm
STABIL RB-A 102- 109 HCP	185 mm	50 mm	109 mm	109 mm	13 mm	152 mm	119 mm	5 mm
STABIL RB-A 109- 115 HCP	192 mm	50 mm	115 mm	115 mm	13 mm	159 mm	125 mm	5 mm
STABIL RB-A 115- 122 HCP	199 mm	50 mm	122 mm	122 mm	13 mm	166 mm	132 mm	5 mm
STABIL RB-A 122- 128 HCP	205 mm	50 mm	128 mm	128 mm	13 mm	172 mm	138 mm	5 mm
STABIL RB-A 128- 134 HCP	211 mm	50 mm	134 mm	134 mm	13 mm	178 mm	144 mm	5 mm
STABIL RB-A 134- 140 HCP	217 mm	50 mm	140 mm	140 mm	13 mm	184 mm	150 mm	5 mm
STABIL RB-A 140- 146 HCP	223 mm	50 mm	146 mm	146 mm	13 mm	190 mm	156 mm	5 mm
STABIL RB-A 146- 152 HCP	230 mm	50 mm	152 mm	152 mm	13 mm	197 mm	162 mm	5 mm
STABIL RB-A 152- 158 HCP	236 mm	50 mm	158 mm	158 mm	13 mm	203 mm	168 mm	5 mm
STABIL RB-A 157- 163 HCP	241 mm	50 mm	163 mm	163 mm	13 mm	208 mm	173 mm	5 mm
STABIL RB-A 163- 169 HCP	255 mm	50 mm	169 mm	169 mm	13 mm	222 mm	185 mm	8 mm
STABIL RB-A 168- 174 HCP	260 mm	50 mm	174 mm	174 mm	13 mm	227 mm	190 mm	8 mm

Pipe Clamp STABIL RB-A HCP

Type	B1	b1	D	D1	d	e	H	t
STABIL RB-A 174- 180 HCP	266 mm	50 mm	180 mm	180 mm	13 mm	233 mm	196 mm	8 mm
STABIL RB-A 181- 187 HCP	273 mm	50 mm	187 mm	187 mm	13 mm	240 mm	203 mm	8 mm
STABIL RB-A 188- 194 HCP	281 mm	50 mm	194 mm	194 mm	13 mm	248 mm	210 mm	8 mm
STABIL RB-A 194- 200 HCP	287 mm	50 mm	200 mm	200 mm	13 mm	254 mm	216 mm	8 mm
STABIL RB-A 201- 207 HCP	294 mm	50 mm	207 mm	207 mm	13 mm	261 mm	223 mm	8 mm
STABIL RB-A 208- 214 HCP	301 mm	50 mm	214 mm	214 mm	13 mm	268 mm	230 mm	8 mm
STABIL RB-A 215- 221 HCP	308 mm	50 mm	221 mm	221 mm	13 mm	275 mm	237 mm	8 mm
STABIL RB-A 222- 229 HCP	316 mm	50 mm	229 mm	229 mm	13 mm	283 mm	245 mm	8 mm
STABIL RB-A 230- 237 HCP	324 mm	50 mm	237 mm	237 mm	13 mm	291 mm	253 mm	8 mm
STABIL RB-A 238- 245 HCP	332 mm	50 mm	245 mm	245 mm	13 mm	299 mm	261 mm	8 mm
STABIL RB-A 246- 254 HCP	341 mm	50 mm	254 mm	254 mm	13 mm	308 mm	270 mm	8 mm
STABIL RB-A 255- 262 HCP	350 mm	50 mm	262 mm	262 mm	13 mm	317 mm	278 mm	8 mm
STABIL RB-A 259- 266 HCP	354 mm	50 mm	266 mm	266 mm	13 mm	321 mm	282 mm	8 mm
STABIL RB-A 266- 273 HCP	361 mm	50 mm	273 mm	273 mm	13 mm	328 mm	289 mm	8 mm
STABIL RB-A 274- 282 HCP	382 mm	60 mm	282 mm	282 mm	17 mm	342 mm	298 mm	8 mm
STABIL RB-A 283- 291 HCP	391 mm	60 mm	291 mm	291 mm	17 mm	351 mm	307 mm	8 mm
STABIL RB-A 292- 300 HCP	400 mm	60 mm	300 mm	300 mm	17 mm	360 mm	316 mm	8 mm
STABIL RB-A 301- 309 HCP	409 mm	60 mm	309 mm	309 mm	17 mm	369 mm	325 mm	8 mm
STABIL RB-A 310- 317 HCP	417 mm	60 mm	317 mm	317 mm	17 mm	377 mm	333 mm	8 mm
STABIL RB-A 317- 324 HCP	425 mm	60 mm	324 mm	324 mm	17 mm	385 mm	340 mm	8 mm
STABIL RB-A 325- 333 HCP	434 mm	60 mm	333 mm	333 mm	17 mm	394 mm	349 mm	8 mm
STABIL RB-A 334- 342 HCP	443 mm	60 mm	342 mm	342 mm	17 mm	403 mm	358 mm	8 mm
STABIL RB-A 343- 350 HCP	451 mm	60 mm	350 mm	350 mm	17 mm	411 mm	366 mm	8 mm
STABIL RB-A 349- 356 HCP	457 mm	60 mm	356 mm	356 mm	17 mm	417 mm	372 mm	8 mm
STABIL RB-A 358- 365 HCP	466 mm	60 mm	365 mm	365 mm	17 mm	426 mm	381 mm	8 mm
STABIL RB-A 366- 374 HCP	475 mm	60 mm	374 mm	374 mm	17 mm	435 mm	390 mm	8 mm
STABIL RB-A 375- 382 HCP	483 mm	60 mm	382 mm	382 mm	17 mm	443 mm	398 mm	8 mm
STABIL RB-A 381- 388 HCP	489 mm	60 mm	388 mm	388 mm	17 mm	449 mm	404 mm	8 mm
STABIL RB-A 389- 396 HCP	497 mm	60 mm	396 mm	396 mm	17 mm	457 mm	412 mm	8 mm
STABIL RB-A 397- 407 HCP	508 mm	70 mm	407 mm	407 mm	17 mm	468 mm	423 mm	8 mm
STABIL RB-A 408- 418 HCP	519 mm	70 mm	418 mm	418 mm	17 mm	479 mm	434 mm	8 mm
STABIL RB-A 419- 429 HCP	530 mm	70 mm	429 mm	429 mm	17 mm	490 mm	445 mm	8 mm
STABIL RB-A 430- 440 HCP	541 mm	70 mm	440 mm	440 mm	17 mm	501 mm	456 mm	8 mm
STABIL RB-A 441- 451 HCP	552 mm	70 mm	451 mm	451 mm	17 mm	512 mm	467 mm	8 mm
STABIL RB-A 447- 457 HCP	558 mm	70 mm	457 mm	457 mm	17 mm	518 mm	473 mm	8 mm

Pipe Clamp STABIL RB-A HCP

Type	B1	b1	D	D1	d	e	H	t
STABIL RB-A 458- 468 HCP	569 mm	70 mm	468 mm	468 mm	17 mm	529 mm	484 mm	8 mm
STABIL RB-A 467- 477 HCP	578 mm	70 mm	477 mm	477 mm	17 mm	538 mm	493 mm	8 mm
STABIL RB-A 477- 487 HCP	588 mm	70 mm	487 mm	487 mm	17 mm	548 mm	503 mm	8 mm
STABIL RB-A 488- 498 HCP	599 mm	70 mm	498 mm	498 mm	17 mm	559 mm	514 mm	8 mm
STABIL RB-A 498- 508 HCP	609 mm	70 mm	508 mm	508 mm	17 mm	569 mm	524 mm	8 mm
STABIL RB-A 509- 519 HCP	620 mm	70 mm	519 mm	519 mm	17 mm	580 mm	535 mm	8 mm
STABIL RB-A 520- 530 HCP	631 mm	70 mm	530 mm	530 mm	17 mm	591 mm	546 mm	8 mm
STABIL RB-A 531- 541 HCP	643 mm	70 mm	541 mm	541 mm	17 mm	603 mm	557 mm	8 mm
STABIL RB-A 542- 552 HCP	654 mm	70 mm	552 mm	552 mm	17 mm	614 mm	568 mm	8 mm
STABIL RB-A 553- 563 HCP	665 mm	70 mm	563 mm	563 mm	17 mm	625 mm	579 mm	8 mm
STABIL RB-A 564- 574 HCP	676 mm	70 mm	574 mm	574 mm	17 mm	636 mm	590 mm	8 mm
STABIL RB-A 575- 585 HCP	687 mm	70 mm	585 mm	585 mm	17 mm	647 mm	601 mm	8 mm
STABIL RB-A 586- 596 HCP	698 mm	70 mm	596 mm	596 mm	17 mm	658 mm	612 mm	8 mm
STABIL RB-A 594- 604 HCP	706 mm	70 mm	604 mm	604 mm	17 mm	666 mm	620 mm	8 mm
STABIL RB-A 600- 610 HCP	712 mm	70 mm	610 mm	610 mm	17 mm	672 mm	626 mm	8 mm

Certification

Documents

RB-A HCP Type Overview