





General Information

Height-adjustable, double-clamp pipe shoe with two bars and a delivery height of 150 mm. Height adjustment in steps of 2.5 mm. When resting on steel beams, a minimum flange width of 80 mm is recommended. These pipe shoes are designed for use in the temperature range 300°C to 500°C. The material-dependent correction values k are used for determining the loads at real operating temperatures. To reach the expected temperatures, according to DIN EN 13480-3, Table 13.11.2–2 must be considered for the substructure.

Installation

To guarantee that both sliding plates rest correctly, both webs must be adjusted to exactly the same height.

Type	Height H as delivered [mm]	Height H Range [mm]
HV 150	150	116 - 168,5

Tightening torque screw connections

Clamping bolts	Tightening torque [Nm]	Height adjustment	Tightening torque [Nm]
DN 200	50	Bolts in the bar	80
DN 250 - 600	60	Bolts in the bar	80

Temperature

Max. temperature	500 °C
------------------	--------

Mechanical Properties

Pipe shoe static coefficient of friction u (without sliding plate) - siFramo and siMotec	0,3
--	-----

Material Properties

Halogen-free	0
UV-resistant	0
Salt spray test	Resistance > 500 hours

Material

Primary element material	steel
Connecting element material	Torque/Nut Height adjustment: A4-80 Torque/Nut Pipe Clamp: A4-70

Surface finish	powder-coated
Corrosion protection class	C4 (>300°C)

Additional information

Delivery time on request - Made-to-order goods.

Types

Type	Size min.	Size max.	DN	Weight	Quantity	Part number
LD-HT-HV 150 266-273 (DN 250_10")	266,00 mm	273,00 mm	DN 250 (10")	14,172 kg/ pcs.	1 pcs.	801194
LD-HT-HV 150 317-324 (DN 300_12")	317,00 mm	324,00 mm	DN 300 (12")	17,055 kg/ pcs.	1 pcs.	801200
LD-HT-HV 150 349-356 (DN 350_14")	349,00 mm	356,00 mm	DN 350 (14")	18,022 kg/ pcs.	1 pcs.	801204
LD-HT-HV 150 397-407 (DN 400_16")	397,00 mm	407,00 mm	DN 400 (16")	20,901 kg/ pcs.	1 pcs.	801210
LD-HT-HV 150 447-457 (DN 450_18")	447,00 mm	457,00 mm	DN 450 (18")	22,26 kg/ pcs.	1 pcs.	801215
LD-HT-HV 150 498-508 (DN 500_20")	498,00 mm	508,00 mm	DN 500 (20")	23,651 kg/ pcs.	1 pcs.	801220
LD-HT-HV 150 600-610 (DN 600_24")	600,00 mm	610,00 mm	DN 600 (24")	26,46 kg/ pcs.	1 pcs.	801230

Dimensions

Type	b	BG1	D	D1	H	HV min	HV max	SL	SG	t	W
LD-HT-HV 150 266-273 (DN 250_10")	50 mm	280 mm	273 mm	273 mm	150 mm	116 mm	168,5 mm	55 mm	M12	5 mm	90°
LD-HT-HV 150 317-324 (DN 300_12")	60 mm	280 mm	324 mm	324 mm	150 mm	116 mm	168,5 mm	60 mm	M16	5 mm	45°
LD-HT-HV 150 349-356 (DN 350_14")	60 mm	320 mm	356 mm	356 mm	150 mm	116 mm	168,5 mm	60 mm	M16	5 mm	45°
LD-HT-HV 150 397-407 (DN 400_16")	70 mm	320 mm	407 mm	407 mm	150 mm	116 mm	168,5 mm	65 mm	M16	5 mm	45°
LD-HT-HV 150 447-457 (DN 450_18")	70 mm	320 mm	457 mm	457 mm	150 mm	116 mm	168,5 mm	65 mm	M16	5 mm	45°
LD-HT-HV 150 498-508 (DN 500_20")	70 mm	320 mm	508 mm	508 mm	150 mm	116 mm	168,5 mm	65 mm	M16	5 mm	45°
LD-HT-HV 150 600-610 (DN 600_24")	70 mm	320 mm	610 mm	610 mm	150 mm	116 mm	168,5 mm	65 mm	M16	5 mm	45°

Certification



Documents



**Sikla Pipe Supports -
Comprehensive Solutions for Secure
and Efficient Installations**