EN

DECLARATION OF PERFORMANCE

No Sikla 0470-A

REGULATION (EU) No 305/2011

Unique identification code of the product-type	Profile Coupling PK 46
Type number	see "Annex"
Intended use	Structural steel work ≤ EXC 2
Manufacturer	Sikla Holding GmbH, Ägydiplatz 3 4600 Thalheim bei Wels | Austria
System of AVCP	System 2+
Harmonised standard	EN 1090-1:2009+A1:2011
Notified body	TÜV Rheinland Industrie Service GmbH | NB 0035

Performance property	**Declared performance**
Tolerances on dimensions and shape	EN 1090-2:2018+A1:2024
Weldability	Not designed for
Fracture toughness / Impact strength	NPD
Load-bearing Capacity	see "Annex"
Deformation in serviceability limit state	NPD
Fatigue strength	NPD
Resistance to Fire	NPD
Reaction to fire	A1 (Stahl) EN 13501-1
Release of Cadmium and its compounds	NPD
Emmision of Radioactivity	NPD
Durability	Hot dip galvanized EN ISO 1461:2009-10

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with REGULATION (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Villingen-Schwenningen, 21.10.2026

Peter Menz | Head of R&D

Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.

Annex

Annex – Sikla Conformed Items

Artikel Nummer *Item Number*	Bezeichnung *Description*
802159	PK 46 HCP

Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.

	Product:	Profile Clip MPK 46
	Description	Internal connecting element for joining two Profiles PRO 46. Particularly suitbale for vertical extension. Should the component be used for horizontal application, the maximum permissible bending moment at the connection point must be observed.
Boundary Conditions:		

$\pm V_{x,Rd}$ [kN]	18,08
$\pm C_{Vx,Rd}$ [kN/mm]	5,39
$\pm C_{Vx,Geb.}$ [kN/mm]	6,36
$\pm M_{y,Rd}$ [kNm]	0,54
$\pm C_{My,Rd}$ [kNm/rad]	46,84
$\pm C_{My,Geb.}$ [kNm/rad]	56,16

Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.