EN

DECLARATION OF PERFORMANCE

No Sikla 0400-A

REGULATION (EU) No 305/2011

Unique identification code of the product-type	Profile PRO 46
Type number	see "Annex"
Intended use	Structural steel work ≤ EXC 2
Manufacturer	Sikla Holding GmbH, Ägydiplatz 3 4600 Thalheim bei Wels | Austria
System of AVCP	System 2+
Harmonised standard	EN 1090-1:2009+A1:2011
Notified body	TÜV Rheinland Industrie Service GmbH | NB 0035

Performance property	**Declared performance**
Tolerances on dimensions and shape	EN 1090-2:2018+A1:2024
Weldability	Not designed for
Fracture toughness / Impact strength	NPD
Load-bearing Capacity	see "Annex"
Deformation in serviceability limit state	NPD
Fatigue strength	NPD
Resistance to Fire	NPD
Reaction to fire	A1 (Stahl) EN 13501-1
Release of Cadmium and its compounds	NPD
Emmision of Radioactivity	NPD
Durability	Continuously hot-dip coated ZM 310 acc. to DIN EN 10346:2015-10

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with REGULATION (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Villingen-Schwenningen, 21.10.2026

Peter Menz | Head of R&D


Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.

Annex

Annex – Sikla Conformed Items

Artikel Nummer *Item Number*	Bezeichnung *Description*
802156	Montageprofil PRO 46 6M HCP
802157	Montageprofil PRO 46 2M HCP
802152	Montageprofil PRO 46-P 6M HCP
802153	Montageprofil PRO 46-P 2M HCP

Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.

	Product:	Profile PRO 46
	Description	Multifunctional profile for creating simple and complex 3D substructures for a wide range of applications. The closed shape not only provides high torsional rigidity but also allows connectivity on all four sides without restrictions. Available in perforated and unperforated profiles.
Boundary Conditions:		

Typ	Elastic modulus [cm^3]	Second moment of area [cm^4]	Radius of gyration Yi [cm]	Torsional constant I_t [cm^4]	Cross-sectional Area A [cm^2]
PRO 46	W_y: 4,12	I_y: 9,49	i_y: 1,60	8,10	3,70
	W_z: 4,12	I_z: 9,49	i_z: 1,60		
PRO 46-P	W_y: 3,46	I_y: 7,96	i_y: 1,55	8,08	3,33
	W_z: 4,11	I_z: 9,45	i_z: 1,68		

Disclaimer:
The original of this declaration of performance was written in German.
In the event of deviations in the translation, the German version shall be valid.