


Cantilever Bracket AK 41 HCP









General Information

Recommended for single-armed wall suspension or fixing to other building structures. Also available as a double version.

Installation

When used in combination with sliding elements, a Tied Rod is absolutely essential for absorbing the forces running along the centre line of the pipe.
For cantilever lengths > 500 mm we recommend the integration of a prop-up.
M12 anchors are fitted into the slotted holes (HP1). Dimensions of the slotted hole: 13mm x 18mm

Mechanical Properties

Permissible stress σ{perm.}	160.00 N/mm²

Material Properties

Halogen-free	0
UV-resistant	0

Material

Primary element material	steel
Surface finish	HCP
Corrosion protection class	C4

Forces

Type	-V{X,perm.}	V{X,perm.}	-V{Y,perm.}	V{Y,perm.}	-V{Z,perm.}	V{Z,perm.}
AK 41/41 - 320 HCP	17.38 kN	17.38 kN	14.41 kN	14.41 kN	24.36 kN	24.36 kN
AK 41/41 - 570 HCP	17.38 kN	17.38 kN	14.41 kN	14.41 kN	24.36 kN	24.36 kN
AK 41/41 - 820 HCP	17.38 kN	17.38 kN	14.41 kN	14.41 kN	24.36 kN	24.36 kN


Moments

Type	-M{Y,perm.}	M{Y,perm.}	-M{Z,perm.}	M{Z,perm.}
AK 41/41 - 320 HCP	0.53 kNm	0.53 kNm	0.5 kNm	0.5 kNm
AK 41/41 - 570 HCP	0.53 kNm	0.53 kNm	0.5 kNm	0.5 kNm
AK 41/41 - 820 HCP	0.53 kNm	0.53 kNm	0.5 kNm	0.5 kNm

Types

Type	LG	Weight	Quantity	Part number
AK 41/41 - 320 HCP	320.5 mm	1 kg/pcs.	10 pcs.	181667
AK 41/41 - 570 HCP	570.5 mm	1.545 kg/pcs.	10 pcs.	181676

Cantilever Bracket AK 41 HCP



Type	LG	Weight	Quantity	Part number
AK 41/41 - 820 HCP	820.5 mm	2 kg/pcs.	1 pcs.	161479

Dimensions

Type	BP	HP	HP1	LG	tP
AK 41/41 - 320 HCP	40 mm	134 mm	100 mm	320.5 mm	8 mm
AK 41/41 - 570 HCP	40 mm	134 mm	100 mm	570.5 mm	8 mm
AK 41/41 - 820 HCP	40 mm	134 mm	100 mm	820.5 mm	8 mm

Certification