


# Support Cone SMD 1









## General Information

Single-point mounting element for use with an anchor for floor, wall and ceiling mounting in M&E services. With its good overall stability, the Support Cone SMD 1 may also be used as a fixed-point mounting element in certain areas. In that case the permissible values for the lateral forces indicated in the characteristic curve are to be taken into consideration. This also applies to wall mounting situations. When used as fixed-point mounting element the pipe clamp is to be connected directly to the support tube. When used as a normal, rigid mounting element, a grub screw may be used between support tube and pipe clamp for height adjustment.

## Mechanical Properties

| | |
|---|---|
| Permissible stress σ{perm.} | 160.00 N/mm² |

## Material Properties

| | |
|---|---|
| Halogen-free | 0 |
| UV-resistant | 0 |

## Material

| | |
|---|---|
| Primary element material | steel |
| Surface finish | electro galvanized (Fe//Zn) |
| Corrosion protection class | C2 |

## Types

| Type | Weight | Quantity | Part number |
|---|---|---|---|
| SMD 1 - 10 | 0.24 kg/pcs. | 25 pcs. | 112382 |
| SMD 1 - 3/4'' | 0.265 kg/pcs. | 25 pcs. | 118134 |

## Certification

## Documents

Loads – Support Cone SMD 1

# Support Cone SMD 1

